ICD&C **PRELIMINARY**

POWER INDUCTOR – PRODUCT DATASHEET


255.0 µH · 75.0 A rms · 125.0 A sat · 15.0 kHz – powder-core toroidal inductor, flying leads

Part number	HPV075-15-511
Revision / date	R1.0 · 2026-11-06
Customer	ICD&C standard series HPV (800 V) – unit 1 of 2
Application	HPV075-15-511 – set of 2 units in series (510 µH), 800 V – sheet = 1 unit
Description	Powder-core toroidal power inductor, Litz-wire winding, flying leads

1. ELECTRICAL CHARACTERISTICS

Parameter	Min.	Typ.	Max.	Unit	Conditions
Inductance L0	234.6	255.0	275.4	µH	10 kHz, 1 V, 0 A DC bias (±8 %)
Inductance at rated peak current		234.6		µH	I = 90.0 A (Irms + ½ ripple)
Inductance at saturation current	204.0			µH	I = Isat = 125.0 A DC
Rated current Irms			75.0	A	continuous, Ta ≤ 85 °C, natural convection
Saturation current Isat	125.0			A	L ≥ 80 % of nominal L0
Ripple current ΔI		30.0		A pk-pk	at 15.0 kHz
Operating frequency		15.0		kHz	ripple / switching frequency
DC resistance DCR		4.72		mΩ	4-wire, 25 °C, at winding exit (leads excl.)
Power loss		47.0		W	Irms + ripple, Ta = 50 °C
Temperature rise ΔT		37		K	rated conditions, Ta = 50 °C, still air
Winding (hot-spot) temperature		124	155	°C	rated conditions, Ta = 85 °C
Operating ambient temperature	-40		85	°C	at rated current
Insulation class		F			winding system 155 °C
Dielectric test					Per agreement with customer
Power rating / max. bus voltage		31.6 kW	844 V		set of 2 units in series (510 µH), D = 0.5 (buck / boost); per unit ≤ 422 V

2. MECHANICAL – GENERAL ARRANGEMENT, Flying leads only (dimensions in mm)





Dimension	Nominal	Min.	Max.	Unit	Note
A – Wound outer Ø	144.0		147	mm	incl. winding
B – Wound height	80.9		83	mm	incl. winding
C – Free inner bore Ø	56.0	53		mm	available for mounting bolt / clamp
D – Lead free length (each)	150	145	155	mm	measured from winding body
E – Strip & tin length	15	13	17	mm	stripped and solder-tinned, no sleeving
F – Lead conductor Ø	7.7			mm	copper Litz wire, reference, over insulation
G – Lead exit angle	30	20	40	°	both leads on the same side
Weight	6311			g	approx.


2b. MOUNTING – none (flying leads only)


Dimension	Nominal	Min.	Max.	Unit	Note
H – Centre / overall height	–		–	mm	foot underside to toroid axis
J – Bracket height	–			mm	–
K – Plate width	–			mm	
L – Foot / base depth	–			mm	
M – Fixing pitch	–			mm	–
N – Fixing hole / slot	–			mm	–
P – Centre bolt	–				–
Q – Pressure disc Ø	–			mm	–
R – Plate thickness	–			mm	–
S – Slot position	–			mm	–
T – Centring boss / bush Ø	–			mm	–
Mounting notes	No mounting hardware supplied. Fix through bore C with an insulated clamp; do not form a closed metal loop through the bore.				

2c. CHARACTERISTIC CURVES (typical, still air)









3. CONSTRUCTION	
Core	Distributed-gap powder toroid, coated, 3 cores stacked
Winding	Copper Litz wire, insulation class F (155 °C); protective tape over the winding (Polyimide 180 °C)
Terminations	Flying leads, stripped and solder-tinned, no sleeving
Mounting	none
Marking	Label with part number, revision and date code
Compliance	RoHS / REACH – to be confirmed

4. ROUTINE TESTS (100 %)		
Test	**Method**	**Acceptance**
Inductance	LCR meter, 10 kHz, 1 V, 0 A	255.0 µH ± 8 %
DC resistance	4-wire, corrected to 25 °C	record value (typ. 4.72 mΩ)
Dielectric	Per agreement with customer	no breakdown or flashover
Visual & dimensions	GA dimensions A–G	within the limits of section 2

5. DOCUMENT	
Prepared by	ICD&C
Revision / date	R1.0 · 2026-11-06

Typ. = calculated design values for reference; Min./Max. = specified limits. Thermal data for natural convection in still air – actual values depend on mounting and cooling. Status: PRELIMINARY. Subject to change without notice.