THREE-PHASE LINE REACTOR · INSULATION CLASS B

# 20 A · uk 2 % · 0.735 mH · 400 V

**Part no. LR3020-50-741-C01** · former type ILR 2/20-400-B · copper winding · class B, Ta 45 °C

| | | |
|---|---|---|
| **0.735 mH**<br>Inductance per phase, ±10 % | **20 A**<br>Rated current, 400 V 50 Hz | **2 %**<br>Voltage drop ΔU 4.6 V |
| **32 A**<br>Linearity current (L ≥ 90 %) | **41 W**<br>Total losses at I_n, Ta 40 °C (calc.) | **ΔT 49 K**<br>Temperature rise at I_n, Ta 40 °C |
| **Class B · Ta 45 °C**<br>IEC 61558-1, winding ≤ 120 °C | **3.6 kg**<br>Weight approx. | **142×95×177**<br>A × B × C (mm), see GA drawing |


## 1 ELECTRICAL SPECIFICATION


| Parameter | Condition | Value | Remark |
|---|---|---|---|
| **Inductance per phase** | 50 Hz, I_n, each phase U1–U2, V1–V2, W1–W2 | 0.735 mH ±10 % | calc. |
| **Rated current I_n** | continuous, Ta ≤ 45 °C | 20 A rms | |
| **Relative voltage drop uk** | at I_n, 400 V 50 Hz | 2 % (4.6 V per phase) | |
| **Linearity** | L at 1.6 × I_n = 32 A | ≥ 0.662 mH (90 %) | typ. 98% |
| **Total losses** | at I_n, Ta 40 °C, all phases | ≤ 47 W | typ. 41 W |
| **Temperature rise** | I_n, Ta 40 °C, natural cooling | ΔT ≈ 49 K | calc. |
| **Insulation class / ambient** | IEC 61558-1, resistance method | B · winding ≤ 120 °C at Ta 45 °C | calc. 94 °C |
| **Hi-pot** | winding – core, 50 Hz, 60 s | 2.5 kV AC | |
| **Rated voltage** | network | 400 V, 50 Hz, 3-phase | for frequency converters / drives |


## 2 DESIGN AND MOUNTING


| Item | Description |
|---|---|
| **Construction** | Three-phase iron-core reactor with air gap, copper winding, vacuum impregnated, open design (IP00) |
| **Terminals** | screw terminals 10 mm², marking U1-V1-W1 (line) / U2-V2-W2 (load), PE stud M6 |
| **Mounting** | 9 × 15 (M8) slots, pitch n1 × n2 = 110 × 65 mm, any position (coils vertical recommended) |
| **Dimensions / weight** | A × B × C = 142 × 95 × 177 mm · ≈ 3.6 kg |
| **Standard** | EN 61558-2-20 · CE · RoHS |

## 3 TYPICAL CHARACTERISTICS (CALC.)








**Notes**


- Curves are design calculations from the B-H and loss curves of the electrical steel and a thermal model (natural convection, altitude ≤ 1000 m).
- Thermal rating: IEC 61558-1 class B at Ta 45 °C (winding ≤ 120 °C, resistance method); type-test values replace "calc." after release.
- Rated current includes typical 6-pulse drive harmonics.

## 4 GENERAL ARRANGEMENT (GA) DRAWING




FRONT VIEW

SIDE VIEW




TOP VIEW (mounting)

| Dim. | Value (mm) | Description |
|---|---|---|
| **A** | 142 | overall width (core / coils) |
| **B** | 95 | overall depth incl. mounting feet |
| **C** | 177 | overall height incl. feet and terminals |
| **D** | 46 | depth of the coils |
| **n1 × n2** | 110 × 65 | mounting hole pitch, slots 9 × 15 (M8) |
| **Terminals** | | screw terminals 10 mm² · PE M6 on foot |

Dimensions in mm. Overall dimensions A, C, D from the design; mounting feet, terminals and hole pitch are ICD&C standard assumptions (indicative) – binding values on the production drawing. Tolerances ±3 mm (overall), ±1 mm (hole pitch). Weight ≈ 3.6 kg.